

TECHNICAL DATA

Shaft Alignment Tablet

General specifications		
CPU	Processor:	Octa-Core (8): 2.2 GHz (2) and 1.8 GHz (6)
	Memory:	4 GB LPDDR4X SDRAM/64 GB UFS Flash
Display	Technology:	Corning® Gorilla® Glass
	Resolution:	600 nits, color WXGA 1280x800
	Dimensions:	8 inch/20.3 cm
Power Supply	Operating time:	Up to 11 Hours
	Battery:	6100 mAh 3.87 V rechargeable Li-Ion Polymer; (23.61 Wh)
	Charging:	USB-C
Connectivity	Wifi:	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w/mc/ax 2x2 MU-MIMO; Wi-Fi® certified; IPv4, IPv6 (Wi-Fi 6)
	Bluetooth:	Bluetooth v5.1 / 2.1+EDR Class 2 (Bluetooth LE)
	RFID:	Integrated RFID with read and write capabilities Docking connector (charge and data) USB-C side port (tablet charging and data only)
Environmental protection	IP 65:	Dustproof and water jets resistant
	Relative humidity:	5% to 95% non-condensing
Drop test	1.2 m (4 ft)	
Temperature range	Operation:	-20°C to 50°C (-4°F to 122°F)
	Storage:	-40°C to 70°C (-40°F to 158°F)
Dimensions	267 mm L x 171 mm H x 35 mm D 10 33/64" x 6 47/64" x 1 3/8"	
Weight	930 g/2.1 lbs	
Camera	Rear:	Image capture: 13 MP auto-focus camera with user controllable LED flash
	Front:	5MP
CE conformity	Refer to the CE compliance certificate in www.pruftechnik.com	
Carrying case	Standard	HPX® Harz, drop tested (2 m / 6 1/2 ft.)
	Dimensions	Approx. 551 x 358 x 226 mm (21 11/16" x 14 3/32" x 8 29/32")
	Weight	Including all standard parts - Approx. 11 kg (24.3 lb)